



Abdichtungssysteme

**DECLARATION OF PERFORMANCE**  
**according Annex III of the Regulation (EU) No 305/2011**  
**amended by Commissions delegated Regulation (EU) No 574/2014**

No. J 236

**1. Unique identification code of the product-type:**

KÖSTER MS Joint Sealant  
0834

**2. Intended use:**

Sealant for facade for interior and exterior application –  
EN 15651-1: F-EXT-INT

**3. Manufacturer:**

KÖSTER BAUCHEMIE AG  
Dieselstraße 1 - 10  
26607 Aurich

**4. Authorised representative:**

Not relevant

**5. Systems for assessment and verification of performance**

System 4  
System 3 for fire behaviour

**6a. Harmonised standard:**

EN 15651-1:2012

**6b. Notified bodies:**

**Materials testing centre for the construction industry**  
Beethovenstraße 52, 38106 Braunschweig  
Identification number 0761  
(fire behaviour)

## 7. Declared performance:

Conditioning: Method A

Base material: [Mortar M1 according to ISO 13640]

Key features	Performance	System for the assessment and verification of constancy of performance	Harmonised technical specification
Fire behaviour	Class E	System 3	EN 15651-1:2012
Release of substances hazardous to the environment and health	see MSDS	System 4	
Water and air tightness			
a) Stability	≤ 3 mm (25 HM)		
b) Volume loss	≤ 10 %		
c) Tensile behaviour (elongation under pre-tensioning after immersion in water at 23°C)	≥ 100 % (25 HM) No failure (NF)		
Resilience	≥ 70 % (25 HM)		
Adhesive and elongation behaviour under pre-tensioning after immersion in water	No failure (NF)		
Adhesion and expansion behaviour at different temperatures	No failure (NF)		
Durability	Passed		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Dr Eike Kunst  
(Research and Development Export)



..... Aurich, 13.8.2024.....

.....  
(Signature)