



KÖSTER Footpump

Foot operated injection pump for the injection of KÖSTER injection resins

Features

The KÖSTER Foot Pump is a reliable foot driven injection pump which is suited for high pressure injection of all KÖSTER injection resins. It is sturdy, easy to use and easy to clean.

Technical Data

Capacity:	approx. 7.5 cm ³ per pass
Operating pressure:	0 – 200 bar
Measurements:	50 cm x 23 cm x 60 cm
Weight:	approx. 12 kg

KÖSTER Accessories

KÖSTER Injection Hose
 KÖSTER Ball Valve
 KÖSTER Manometer
 KÖSTER Material Hopper
 KÖSTER Fine Sieve
 KÖSTER Mautrol 2C
 KÖSTER Mautrol Flex 2C

Prod. code IN 929 002
 Prod. code IN 929 003
 Prod. code IN 929 004
 Prod. code IN 929 005
 Prod. code IN 929 007
 Prod. code M 261
 Prod. code M 262 020

Fields of Application

High pressure injection of:

- KÖSTER IN 1
- KÖSTER N 2 / IN 2 HT
- KÖSTER IN 3 / IN 3 HT
- KÖSTER IN 4
- KÖSTER IN 5
- KÖSTER IN 7
- KÖSTER 2IN1
- KÖSTER Mautrol 2C
- KÖSTER Mautrol 2C Flex
- KÖSTER KB-Pox IN

Cleaning

Clean tools immediately after use with KÖSTER Universal Cleaner.

Packaging

IN 958 001 piece

Other

Basic equipment / scope of delivery:

- Manometer 0 - 200 bar
- 6 Liter material hopper
- Lid
- 3 m HD-Material hose with inner diameter 6 mm
- HD-Ball valve with mouthpiece

Related products

KÖSTER IN 1	Prod. code IN 110
KÖSTER 2 IN 1	Prod. code IN 201
KÖSTER IN 2	Prod. code IN 220
KÖSTER IN 3	Prod. code IN 230
KÖSTER KB-Pox IN	Prod. code IN 231
KÖSTER IN 4	Prod. code IN 240
KÖSTER IN 5	Prod. code IN 250
KÖSTER IN 7	Prod. code IN 270
KÖSTER Impact Packer 12 mm x 70 mm	Prod. code IN 903 001
KÖSTER Superpacker 13 mm x 115 mm	Prod. code IN 915 001
CH	
KÖSTER One-Day-Site Packer 13 mm x	Prod. code IN 922 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.